



Classic SIP Corded Phone

1-Line S1210
2-Line S1220



Contemporary SIP Corded Phone

1-Line S2210
2-Line S2220

Following with tradition, the SIP compatible hotel phones offer refreshing styling.

Features

- 1 or 2 lines with line indication
- Standard 12-digit keypad
- Up to 10 programmable guest service keys
- Up to 5 feature buttons - Flash, Hold, Mute, Redial and Conference
- Automatic expired redial memory for guest privacy
- Visual Message Waiting Indicator
- Ergonomic handset design
- Selectable ring tones
- Enhanced speakerphone
- Multi-step volume control (ringer, handset and speakerphone)
- Fully customizable faceplates with large printable area
- Supports desktop or wall mount
- Textured finish resists smudges
- Standard IEEE802.3af Power over Ethernet
- Antibacterial surface
- USB charging port
- 2 year limited warranty

Specifications

Network Features:

- 10/100Mbps switched-port for HSIA
- Supports 802.1pQ priority and VLAN tagging
- Support IEEE802.1x (MD5, TLS and PEAP)
- HTTP
- DHCP
- DNS (A-Record and SRV Record)
- NAPSTR
- SNTP
- SIP (RFC3261 Compliance)
- Supports both in-band (RFC2833) and out-of-band DTMF signaling
- Supports G.711u, G.711a and G.729
- Supports wideband codec
- User friendly web portal for phone configuration and firmware upgrade
- Optional centralized administrative server to assist deployment, monitoring and administration

Power Source: IEEE802.3af PoE Class 2

Humidity: 65% ± 20%

Temperature: 25° C ± 10° C

Colors: Classic - Ash or Black
Contemporary - Pearl or Black

Master Pack: 12 Carton

Certifications:

- ADA Compliant
- FCC Part 15 Class B
- FCC Part 68
- IC
- CE
- ETL
- RoHS Compliant

Cords:

- Coil cord
- 10 foot Cat5e Ethernet Cord

Weight: 2.2 lbs.

Classic Dimensions: 8.6 in. x 6.0 in. x 2.6 in.

Contemporary Dimensions: 7.9 in. x 6.0 in. x 3.8 in.

VHP 20110810



Classic SIP Cordless Phone

1-Line S1410
2-Line S1420



Contemporary SIP Cordless Phone

1-Line S2410
2-Line S2420

The DECT cordless handset with speakerphone integrated into the SIP compatible hotel phone offers 2-line operation with more freedom and comfort than ever before.

Features

- 1 or 2 lines with line indication
- WiFi friendly DECT technology with adjustable coverage area to improve clarity
- Auto registration of cordless handset
- Supports multiple handsets (up to 4)
- Standard 12-digit keypad
- Up to 10 programmable guest service keys
- Up to 5 feature keys - Flash, Hold, Mute, Redial and Conference
- Automatic expired redial memory for guest privacy
- Visual Message Waiting Indicator
- Ergonomic handset design
- Selectable ring tones
- Enhanced handset speakerphone
- Multi-step volume control (ringer, handset and speakerphone)
- Fully customizable faceplates with large printable area
- Supports desktop or wall mount
- Textured finish resists smudges
- Standard IEEE802.3af Power over Ethernet
- Antibacterial surface
- Low battery indicator on handset
- On-cradle charging indicator
- Concealed antenna prevents breakage
- USB charging port
- Battery life of up to 7 hours talk time with 7 days standby
- 2 year limited warranty

Specifications

Network Features:

- 10/100Mbps switched port for HSIA
- Support IEEE802.1pQ priority and VLAN tagging
- Support IEEE802.1x (MD5, TLS and PEAP)
- HTTP
- DHCP
- DNS (A-Record and SRV Record)
- NAPSTR
- SNTP
- SIP (RFC3261 Compliance)
- Supports both in-band (RFC2833) and out-of-band DTMF signaling
- Supports G.711u, G.711a and G.729
- Supports wideband codec
- User friendly web portal for phone configuration and firmware upgrade
- Optional centralized administrative server to assist deployment, monitoring and administration

- Radio Frequency baseband: Available in both DECT 1.8 and DECT 6.0

Power Source: IEEE802.3af PoE Class 2

Humidity: 65% ± 20%

Temperature: 25° C ± 10° C

Colors: Classic - Ash or Black

Contemporary - Pearl or Black

Master Pack: 12 Carton

Certifications:

- ADA Compliant
- FCC Part 15 Class B
- FCC Part 68
- IC
- CE
- ETL
- RoHS Compliant

Cord:

- 10 foot Cat5e Ethernet Cord

Weight: 2.2 lbs.

Classic Dimensions: 8.6 in. x 6.0 in. x 2.6 in.

Contemporary Dimensions:
7.9 in. x 6.0 in. x 3.8 in.

VHP 20110810



Classic SIP Corded Lobby Phone

1-Line S1100



Contemporary SIP Corded Lobby Phone

1-Line S2100

One line SIP lobby phones with your choice of design. Classic styling maintains a traditional look and feel, while contemporary styling offers a refreshing, elegant look.

Features

- 1 line
- Ergonomic handset design
- Fully customizable faceplates with large printable area
- Standard IEEE802.3af Power over Ethernet
- Supports desktop or wall mount
- Textured finish resists smudges
- Antibacterial surface
- 2 year limited warranty

Specifications

Network Features:

- 10/100Mbps switched port for HSIA
- Support IEEE802.1pQ priority and VLAN tagging
- Support IEEE802.1x (MD5, TLS and PEAP)
- HTTP
- DHCP
- DNS (A-Record and SRV Record)
- NAPSTR
- SNTP
- SIP (RFC3261 Compliance)
- Supports both in-band (RFC2833) and out-of-band DTMF signaling
- Supports G.711u, G.711a and G.729
- Supports wideband codec
- User friendly web portal for phone configuration and firmware upgrade
- Optional centralized administrative server to assist deployment, monitoring and administration

Power Source: IEEE802.3af PoE Class 2

Humidity: 65% ± 20%

Temperature: 25° C ± 10° C

Colors: Classic - Ash or Black

Contemporary - Pearl or Black

Master Pack: 12 carton

Certifications:

- ADA Compliant
- FCC Part 15 Class B
- FCC Part 68
- IC
- CE
- ETL
- RoHS Compliant

Cords:

- 6 foot standard coil cord
- 10 foot Cat5e Ethernet Cord

Weight: 2.2 lbs.

Classic Dimensions: 8.6 in. x 6.0 in. x 2.6 in.

Contemporary Dimensions:
7.9 in. x 6.0 in. x 3.8 in.

VHP 20110810



Classic SIP Cordless TrimStyle Phone with Tethered Handset

1-Line S1310
2-Line S1320



Contemporary SIP Cordless TrimStyle Phone with Tethered Handset

1-Line S2310
2-Line S2320

The SIP compatible TrimStyle phone continues to offer an elegant design for both a courtesy or washroom telephone while maintaining comfort and functionality.

Features

- 1 or 2 lines with line indication
- Visual Message Waiting Indicator
- Standard 12-digit keypad
- Handset volume control
- WiFi friendly DECT technology with adjustable coverage area to improve clarity
- Supports desktop or wall mount
- Antibacterial surface
- Textured finish reduces smudges
- Requires pairing with cordless room phone (cannot operate independently)
- 2 Year Warranty

Specifications

Power Source: IEEE 802.3af PoE

Humidity: 65% ± 20%

Temperature: 25° C ± 10° C

Colors: Classic - Ash or Black

Contemporary - Pearl or Black

Master Pack: 12 Carton

Certifications:

- FCC Part 68, FCC Part 15

- IC

- UL 60950

- CE

- ADA Compliant

- RoHS Compliant

Cords:

- 4 foot coil cord

- 10 foot CAT 5 Ethernet Cord

Weight: 1.1 lbs.

Dimensions:

8.5 in. x 3.1 in. x 3.2 in.

VHP 20110810